



IP65 CLASS I CE

SIRIUS LED

A cost-effective LED projector available in multiple outputs, beam angles and finishes.

SIRIUS LED

FEATURES & BENEFITS

- > Various lumen outputs up to 5376lm
- > Excellent thermal management. Suitable for ambient temperatures from -40°C to $+60^{\circ}\text{C}$
- > Average rated LED life: $>50,000\text{hrs}$ (L80/B10)
- > Wall mounting bracket with double pivot design for maximum adjustability ($2 \times 180^{\circ}$)
- > Fixing base plate 170 degree rotation

PERFORMANCE



Light source	LED
Distribution	Symmetric
LED output	4020 - 6550lm
Luminaire output	3216 - 5240lm
CRI	>80

MATERIALS

Body	Die-cast aluminium
Finish	Grey / White / Black
Reflector	Alunova with spherical facets
Diffuser	Clear tempered glass with silicone gaskets
External fixings	Stainless steel screws
Driver	Tridonic (integral)

OPTIONS

- > Anti-glare honeycomb
- > Die-cast aluminium spike and IP68 connector
- > 4000K and lower outputs on request
- > Coloured filters - red, yellow, blue and green



LAMP	COLOUR TEMP	LUMENS	BEAM ANGLE	GREY	WHITE	BLACK
25W	3000K	3216lm	15°	76100101	76100201	76100301
25W	3000K	3216lm	36°	76100401	76100501	76100601
25W	3000K	3216lm	60°	76100701	76100801	76100901
33W	3000K	4064lm	15°	76101001	76101101	76101201
33W	3000K	4064lm	36°	76101301	76101401	76101501
33W	3000K	4064lm	60°	76101601	76101701	76101801
45W	3000K	5240lm	15°	76102801	76102901	76103001
45W	3000K	5240lm	36°	76103101	76103201	76103301
45W	3000K	5240lm	60°	76103401	76103501	76103601