







































LAMP INFORMATION

NAME	LAMP TYPE	BASE	BALLAST			POWER W	FLUX lm	LIFE hrs	L max mm	
			MAG	MAG + START	E.B.					
CFLi			E27			9	400	10000	100	
					INT.	INT.	11	600	10000	110
							15	900	10000	115
							20	1200	10000	125
							23	1400	10000	140
							27	1700	10000	140
							42	2600	10000	145
TC-S			G23	•		5	250	8000	85	
				•		7	400	8000	115	
				•		9	600	8000	145	
				•		11	900	8000	215	
TC-SE			2G7	•	•	5	250	8 / 10000	85	
				•	•	7	400	8 / 10000	115	
				•	•	9	600	8 / 10000	145	
				•	•	11	900	8 / 10000	215	
TC-L			2G11	•	•	18	1200	8 / 10000	225	
				•	•	24	1800	8 / 10000	320	
				•	•	36	2900	8 / 10000	415	
					•	40	3500	10000	535	
					•	55	4800	10000	535	
TC-F			2G10	•	•	18	110	8 / 10000	122	
				•	•	24	1700	8 / 10000	165	
				•	•	36	2800	8 / 10000	217	
TC-D			G24d-1	•		12	900	8000	130	
			G24d-2	•		18	1200	8000	140	
			G24d-3	•		26	1800	8000	160	
TC-DE			G24q-1	•	•	13	900	8 / 10000	130	
			G24q-2	•	•	18	1200	8 / 10000	140	
			G24q-3	•	•	26	1800	8 / 10000	160	
TC-TE			GX24-q1		•	13	900	8 / 10000	90	
			GX24-q2		•	18	1200	8 / 10000	110	
			GX24-q3		•	26	1800	8 / 10000	130	
			GX24-q3		•	32	2400	8 / 10000	145	
			GX24-q4		•	42	3200	8 / 10000	155	
TC-DD			GR8	•		16	1050	10000	138 x 141	
				•		28	2050	10000	205 x 107	
			GR10q	•	•	10	650	10000	92 x 95	
				•	•	16	1050	10000	138 x 141	
				•	•	21	1350	10000	138 x 141	
				•	•	28	2050	10000	205 x 207	
				•	•	38	2850	10000	205 x 207	
				•	•	55	4000	10000	205 x 207	

LAMP INFORMATION

NAME	LAMP TYPE	BASE	BALLAST			POWER W	FLUX lm	LIFE hrs	L max mm		
			MAG	MAG + START	E.B.						
T8			G13	•	•	15	950	9 / 12000	438		
				•	•	18	1350	9 / 12000	590		
				•	•	30	2350	9 / 12000	895		
				•	•	36	3350	9 / 12000	1200		
				•	•	58	5200	9 / 12000	1500		
T5			G5	•	•	6	240	16 / 18000	212		
				•	•	8	330	16 / 18000	298		
				•	•	13	650	16 / 18000	517		
				•	•	14	1200	16 / 18000	549		
				•	•	21	1900	16 / 18000	1149		
				•	•	24	1750	16 / 18000	1449		
				•	•	28	2600	16 / 18000	849		
				•	•	35	3320	16 / 18000	1449		
				•	•	39	3100	16 / 18000	1149		
				•	•	49	4300	16 / 18000	1449		
				•	•	54	4450	16 / 18000	1149		
				•	•	80	6150	16 / 18000	1449		
				HST (SON)			E27	•	•	50	4400
•	•	70	6000					24000	156		
	E40	•	•			100	10000	24000	210		
		•	•			150	14500	24000	210		
		•	•			250	27000	24000	257		
HSE (SON)			E27	•	•	50	3500	24000	156		
				•	•	70	5600	24000	156		
			E40	•	•	100	9500	24000	183		
				•	•	150	14000	24000	226		
				•	•	250	25000	24000	226		
				•	•	400	47000	24000	290		
HIT (MH)			E27	•	•	70	6300	15000	155		
				•	•	100	8800	15000	210		
			E40	•	•	150	13500	15000	210		
				•	•	250	20000	15000	226		
				•	•	400	32000	15000	285		
HIE (MH)			E27	•	•	70	5000	15000	141		
				•	•	100	8000	15000	141		
				•	•	150	12500	15000	141		
			E40	•	•	250	24000	15000	226		
HIT (MH)			G8.5	•	•	20	1700	12000	80		
					G12	•	•	35	3500	12000	100
						•	•	70	7000	12000	100
						•	•	100	9500	12000	105
						•	•	150	14500	12000	105